



Product Type	Outdoor Display (Kiosk)				
Standard Model	H325SSV	H467SSV	H467SDV (Double)	H469SSV	
Touch Screen Model	H325SSI	H467SSI	H467SDV(Double)	H469SSI	
Panel	Screen Size	32"	46"	46" x 2	46"
	Active Display Area (inch/mm)	15.47 x 27.50 / 392.85 x 698.4	22.54 x 40.09 / 572.67 x 1018.08	22.54 x 40.09 / 572.67 x 1018.08	22.54 x 40.09 / 572.67 x 1018.08
	Resolution	1080 x 1920			
	Aspect Ratio	16 : 9			
	Display Colors	16.7 M			
	Brightness (cd/m <sup>2</sup> ; typ)	2,000	2,500	2,500	5,000
	Contrast Ratio	1,300 : 1	5,000 : 1	5,000 : 1	4,000 : 1
	Response Time (ms; GTG)	25	8	8	8
	Viewing Angle (H/V)	178°/178°			
	Life Time (hours)	30,000	50,000	50,000	50,000
Backlight type	LED	LED	LED	LED	
Touch Screen	Response Time (ms)	8~9	8~9	8~9	8~9
	Interface	USB 2.0			
	Touch Intensity	表面保護ガラス			
	Detection Method	静電容量方式			
	Operating System	Windows			
Input	1x VGA (D-Sub)   1x HDMI   1x DVI   1x RS232C [ Double Model; 2x VGA (D-Sub)   2x HDMI   2x DVI   2x RS232C ]				
Power	Operating Voltage	100 - 120V AC, 220 - 240V AC			
	Consumption (typ.)	145 W	400 W	800 W	450 W
	Consumption per nits	0.12 W (max.)	0.16 W (max.)	0.32 W (max.)	0.18 W (max.)
	Heater Block	Max 850 W / Peak 1.2 KW			
Features	Auto Cooling System	Yes			
	Auto Heating System	Yes			
	Anti-Vandal Glass	Yes			
	Anti Reflection Coating	Yes			
	Auto Brightness Sensor	Yes			
Dimension	Set (W x H x D) - inch/mm	26.6 x 66.93 x 5.9 / 675.3 x 1700 x 150	33.66 x 78.74 x 5.9 / 855 x 2000 x 150	33.66 x 78.74 x 12.6 / 855 x 2000 x 320	33.66 x 78.74 x 5.9 / 855 x 2000 x 150
	Weight	Set (lb/kg)	146.6 / 66.5	330.7 / 150	T.B.D
Weight	Set (lb/kg)with touch	T.B.D	335.1 / 152	T.B.D	335.1 / 152
	Surface Treatment	Powder coated (RAL7040)			
Temperature	Operation (°C)	-30 ~ 50			
	Storage (°C)	-40 ~ 60			
Humidity	Non-condensing (%)	20 ~ 80			
Approvals	Ingress Protection	IP66			



Product Type	Outdoor Display (Kiosk)				
Standard Model	H469SDV(Double)	H557SSV	H557SDV(Double)	H757SSV	
Touch Screen Model	H469SDV(Double)	H557SSI	H557SD(Double)	-	
Panel	Screen Size	46" x 2	55"	55" x 2	75"
	Active Display Area (inch/mm)	22.54 x 40.09 / 572.67 x 1018.08	26.79 x 47.62 / 680.4 x 1209.6	26.79 x 47.62 / 680.4 x 1209.6	26.79 x 47.62 / 680.4 x 1209.6
	Resolution	1080 x 1920			
	Aspect Ratio	16 : 9			
	Display Colors	16.7 M			
	Brightness (cd/m <sup>2</sup> ; typ)	5,000	2,500	2,500	2,500
	Contrast Ratio	4,000 : 1	5,000 : 1	5,000 : 1	5,000 : 1
	Response Time (ms; GTG)	8	8	8	8
	Viewing Angle (H/V)	178°/178°			
	Life Time (hours)	50,000	50,000	50,000	50,000
Backlight type	LED	LED	LED	LED	
Touch Screen	Response Time (ms)	8~9	50~100	50~100	50~100
	Interface	USB 2.0			
	Touch Intensity	Permanent (protected by glass)			
	Detection Method	PCT			
	Operating System	Windows			
Input	1x VGA (D-Sub)   1x HDMI   1x DVI   1x RS232C [ Double Model; 2x VGA (D-Sub)   2x HDMI   2x DVI   2x RS232C ]				
Power	Operating Voltage	100 - 120V AC, 220 - 240V AC			
	Consumption (typ.)	900 W	500 W	1 KW	750 W
	Consumption per nits	0.36 W (max.)	0.16 W (max.)	0.32 W (max.)	0.3 W (max.)
	Heater Block	Max 1.7 KW / Peak 2.4 KW	850 W / Peak 1.2 KW	Max 1.7 KW / Peak 2.4KW	Max 1.7 KW / Peak 2.4KW
Features	Auto Cooling System	Yes			
	Auto Heating System	Yes			
	Anti-Vandal Glass	Yes			
	Anti Reflection Coating	Yes			
	Auto Brightness Sensor	Yes			
Dimension	Set (W x H x D) - inch/mm	33.66 x 78.74 x 12.6 / 855 x 2000 x 320	38.0 x 85.8 x 6.3 / 965 x 2180 x 160	38.0 x 85.8 x 12.6 / 965 x 2180 x 320	48.2 x 88.6 x 9.1 / 1225 x 2250 x 230
	Weight	Set (lb/kg)	T.B.D	385.8 / 175	727.5 / 330
Weight	Set (lb/kg)with touch	T.B.D	390.2 / 177	727.5 / 330	592.25 / 270
	Surface Treatment	Powder coated (RAL7040)			
Temperature	Operation (°C)	-30 ~ 50			
	Storage (°C)	-40 ~ 60			
Humidity	Non-condensing (%)	20 ~ 80			
Approvals	Ingress Protection	IP66			

※ 価格：オープン価格  
 ※ 製品の規格及び外観は改良のため予告なく変更される場合があります。  
 詳しくは当社営業担当までお問い合わせ下さい。